

SAFETY DATA SHEET DE - ICER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name DE - ICER

Product number DI500, DI500CZ/SK, DI500NL/F, DI500SCAN, DI500SP/P, DI500SW/F, DI500VX, VP4WC

Internal identification IB/NA/6897

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses De-icing preparation

1.3. Details of the supplier of the safety data sheet

Supplier Autoglym

Works Road Letchworth Herts SG6 1LU

UK

sds@autoglym.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1462 489498 (24Hrs)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Not Classified

2.2. Label elements

Pictogram





Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

DE - ICER

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention.

Contains Propan-2-ol

Supplementary precautionary P501 Dispose of contents/ container in accordance with national regulations.

statements

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Propan-2-ol 60-100%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-

2119457558-25-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

Ethanediol 10-30%

CAS number: 107-21-1 EC number: 203-473-3 REACH registration number: 01-

2119456816-28-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn;R22

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing.

Ingestion Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not

enter the lungs. Get medical attention immediately.

Skin contact Wash skin thoroughly with soap and water or use an approved skin cleanser.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation The product contains organic solvents. Vapours may cause drowsiness and dizziness.

Ingestion May cause discomfort. Nausea, vomiting. Diarrhoea.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

DE - ICER

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Flammable liquid and vapour. Vapours are heavier than air and may spread near ground and

travel a considerable distance to a source of ignition and flash back.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Toxic

gases or vapours. Carbon dioxide (CO2). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during

firefighting

Do not use water jet as an extinguisher, as this will spread the fire. Keep upwind to avoid

inhalation of gases, vapours, fumes and smoke.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes and clothing. No smoking, sparks, flames or other sources of

ignition near spillage. Avoid inhalation of vapours.

6.2. Environmental precautions

Environmental precautions Do not allow to enter drainage system, surface or ground water.

Prevent material from reaching sewage system, holes and cellars.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb small quantities with paper towels and evaporate in a safe place. Absorb spillage with

non-combustible, absorbent material. No smoking, sparks, flames or other sources of ignition

near spillage.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions For personal protection, see Section 8.

Advice on general Do no

Do not eat, drink or smoke when using this product. Provide eyewash station. Wash hands

occupational hygiene thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at room temperature. Store in accordance with local regulations.

7.3. Specific end use(s)

DE-ICER

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Propan-2-ol

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

Ethanediol

Long-term exposure limit (8-hour TWA): WEL 20 ppm 52 mg/m³ vapour Short-term exposure limit (15-minute): WEL 40 ppm 104 mg/m³ vapour

Sk

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

Sk

WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Avoid inhalation of vapours.

Eye/face protection Wear eye protection.

Hand protection Wear protective gloves. The breakthrough time for any glove material may be different for

different glove manufacturers.

Hygiene measures Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Colourless.

Odour Alcoholic.

pH Not applicable.

Flash point ~ 16°C Setaflash closed cup.

Relative density ~ 0.857

Solubility(ies) Completely soluble in water.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

DE-ICER

Possibility of hazardous

reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

None at ambient temperatures.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 2,120.44

Serious eye damage/irritation

Serious eye damage/irritation Irritation of eyes is assumed.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity Not determined.

12.2. Persistence and degradability

Phototransformation Not determined.

Stability (hydrolysis) Not determined.

Biodegradation Expected to be readily biodegradable.

Biological oxygen demand Not determined.

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste, residues, empty containers, discarded work clothes and contaminated cleaning

materials should be collected in designated containers, labelled with their contents.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

DE - ICER

UN No. (ADN)	1993
--------------	------

14.2. UN proper shipping name

Proper shipping name

FLAMMABLE LIQUID, N.O.S. (Isopropanol)

(ADR/RID)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (Isopropanol)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (Isopropanol)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (Isopropanol)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group

ADN packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number 33

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

DE - ICER

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 23/04/2015

Revision 10

SDS number 20931

Hazard statements in full H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Signature Daniel Higgs

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.